

Super Lube®



SUPER LUBE® EXTRA LIGHTWEIGHT OIL

SUPER LUBE® EXTRA LIGHTWEIGHT OIL

Super Lube® Extra Lightweight Oil is engineered for wide temperature applications (-40°F to 500°F).

It exhibits excellent performance in high pressure vane, piston and gear pumps, providing longer life and optimum performance. It has excellent oxidation resistance allowing extension of oil filter intervals while assuring a clean system. The oil has excellent demulsibility qualities in applications where systems are contaminated with small amounts of water.



Super Lube® Extra Lightweight Oil Typical Applications:

- ▶ General light oil applications
- ▶ Textile spindles
- ▶ Grinder arbor bearings
- ▶ Ring oiled bearings
- ▶ Wick feeds
- ▶ Bottle and air line oilers
- ▶ Oil cups
- ▶ Enclosed chains
- ▶ Light circulating systems
- ▶ Food grade chain lubricant



Synco Chemical Corporation - Super Lube®
24 DaVinci Drive, Bohemia, NY 11716
Tel: (631) 567-5300 / Fax: (631) 567-5359
Email: info@super-lube.com / www.super-lube.com



December 13, 2011/ Copyright ©



SUPER LUBE® EXTRA LIGHTWEIGHT OIL

Benefits:

- ▶ Wide Temperature Range
- ▶ Non-toxic (USDA Rating H-1)
- ▶ Long Lasting
- ▶ High Viscosity Index
- ▶ Waterproof
- ▶ Superior at low temperatures
- ▶ Prevents rust and corrosion
- ▶ Good Water Separation



Typical Properties		
Test	Test Method	Rating
Color		Translucent
Viscosity	ASTM D445	
cSt @ 100 C		5.88
SUS @ 40°C		150
Temperature Range		-40°F to 500°F
ISO grade		32
Replaces ISO grades		32-46
Replaces SAE grade oils		80W
Viscosity index		129.25
Warranty		24 months

While the information contained herein is believed to be reliable, Synco Chemical Corporation makes no representation as to the reliability of the results the buyer or user will achieve.

Part No.	Description
53040	1 Gallon
53050	5 Gallon
53550	55 Gallon



Synco Chemical Corporation - Super Lube®
 24 DaVinci Drive, Bohemia, NY 11716
 Tel: (631) 567-5300 / Fax: (631) 567-5359
 Email: info@super-lube.com / www.super-lube.com

