

**Super
Lube®**



SUPER LUBE® FIRE RESISTANT HYDRAULIC OIL

SUPER LUBE® FIRE RESISTANT OIL

Super Lube® FIRE RESISTANT HYDRAULIC OIL

Is an extra high performance water-glycol hydraulic fluid (group 1HF-C) that provides excellent protection from rust and vapor phase corrosion.

Even when sprayed at pressures over 200 bar / 3000 psi, it will not ignite.

Super Lube® Fire Resistant Hydraulic Oil

Features:

- ▶ Outstanding fire resistance
- ▶ Excellent lubricity
- ▶ Good low temperature fluidity
- ▶ High viscosity index
- ▶ Excellent anti wear performance
- ▶ Good storage stability

Applications:

- ▶ Die casting machines
- ▶ Furnace door openers
- ▶ Glass drawing equipment
- ▶ Rod, tube and strip mills
- ▶ Furnace chargers
- ▶ Hot metal shears



Synco Chemical Corporation - Super Lube®
24 DaVinci Drive, Bohemia, NY 11716
Tel: (631) 567-5300 / Fax: (631) 567-5359
Email: info@super-lube.com / www.super-lube.com

June 26, 2003 / Copyright ©



**Super
Lube®**



SUPER LUBE® FIRE RESISTANT HYDRAULIC OIL

SUPER LUBE® FIRE RESISTANT OIL

Typical Properties:

Test Description	ASTM	Typical Properties
Water Content	D-1744	38-40%
Pour Point	D-97	-75°F
Viscosity Index	D-2270	185
Viscosity @100F	D-88	40-46 cSt
Four Ball Wear	D-4172	<0.60mm
Hydraulic Vane Pump	D-2882	80mg Max.
Rust Prevention	D-665	Pass A
Hydraulic Group Class		Group 1 HF-C
Color		Red

Part No.	Description
86050	5 gallon Pail
86055	55 gallon Drum



Synco Chemical Corporation - Super Lube®
24 DaVinci Drive, Bohemia, NY 11716
Tel: (631) 567-5300 / Fax: (631) 567-5359
Email: info@super-lube.com / www.super-lube.com
June 26, 2003 / Copyright ©

