



Super Lube H3 Direct Food Contact Oil

SUPER LUBE® DIRECT FOOD CONTACT H3 OIL

Super Lube H3 Direct Food Contact Oil is a revolutionary new lightweight 8-10 cSt oil that can be used in direct food contact applications in Meat and Poultry as well as all types of food manufacturing facilities. It is ideal for misting, dripping, coating, and protecting metal.

Super Lube H3 Direct Food Contact Oil Typical Applications

- > **General Light Oil Applications**
- > **Food Grade Chain Lubricant**
- > **Meat Hook Lubricant**
- > **Conveyers**
- > **Metal Protectant**
- > **Oil Feeder applications**
- > **Enclosed Chains**
- > **Direct food equipment Lubricant**





Super Lube H3 Direct Food Grade Lubricant



Benefits:

- Viscosity Stable
- Non Toxic USDA/NSF H3 Rated
- Protects metal
- > Reduces Friction and wear
- > Wide Temperature Range
- > Direct food contact safe

Typical Properties

Test	Test Method	Typical Result
Color		Translucent Clear
Viscosity	ASTM D445	
cSt @ 100C		8-10
cSt @ 40C		50-70
Temperature Range		-10°F to 450°F
ISO Grade		46-100
Viscosity Index		145

While the information contained herein is believed to be reliable...Synco Chemical Corporation makes no representation as to the reliability of the results the buyer or user will achieve

Part Number	Description
60004	4oz. Bottle
60016	16oz. Bottle
60032	32oz. Bottle
60040	1 Gal. Bottle
60050	5 Gal. Container
60550	55 Gal. Drum