

SUPER LUBE® OIL W/PTFE

SUPER LUBER OIL W/PTFE

Super Lube® Oil with PTFE is a premium synthetic oil with suspended PTFE particles that bond to surfaces of moving parts.

Super Lube® Oil with PTFE is used as a general purpose lubricant for industrial machinery and equipment.

Super Lube® Oil with PTFE provides protection against friction, wear, rust and corrosion. Machinery lasts longer, downtime is reduced, and productivity is increased.

Super Lube® Oil with PTFE is safe on metal, rubber, plastic, wood, leather, fabric and painted surfaces.



Super Lube® Oil with PTFE Typical Applications:

- ▶ Plain, anti-friction and roller bearings
- Reciprocating compressor lubricant additive
- Machine ways
- Reciprocating compressor lubricant additive
- Machine tools
- Centralized lubricating systems

- ► Straight, helical, bevel and spiral gears
- ► Enclosed industrial gears
- Chains
- Gear head motors
- Conveyors









SUPER LUBE® OIL W/PTFE

Benefits:

- ▶ Waterproof
- Non-toxic (USDA Rating H-1)
- ► Synthetic with PTFE
- ▶ Reduces friction and wear

- ▶ Extends machinery and equipment life
- ▶ Reduces maintenance
- ▶ Viscosity stable
- ▶ Long Lasting

Ту	pical Properties	
Test	Test Method	Rating
Color		Translucent White
Viscosity	ASTM D445	
cSt @ 100°C		14-17
cSt @ 40°C		118-122
ISO grade		220
Replaces ISO grades		150-320
Replaces SAE grade oils		90
Viscosity index		145
Shelf life		24 months

While the information contained herein is believed to be reliable, Synco Chemical Corporation Chemical Corporation makes no representation as to the reliability of the results the buyer or user will achieve.

Part No.	Description
51010	1/4oz Oiler
51004	4 oz Bottle
51014	Oiler Bulk
51040	1 Gallon
51050	5 Gallon
51550	55 Gallon





Synco Chemical Corporation - Super Lube® 24 DaVinci Drive, Bohemia, NY 11716
Tel: (631) 567-5300 / Fax:(631) 567-5359
Email: info@super-lube.com / www.super-lube.com

