

# Super Lube®



## SUPER LUBE® LIGHTWEIGHT OIL

# SUPER LUBE® LIGHTWEIGHT OIL

**Super Lube® Synthetic Lightweight Oil** has a lower viscosity than Super Lube® Oil with PTFE and should be used in place of conventional 8 – 10 cSt oils. It is ideal for misting, dripping, spindle oil applications, and as a food-grade chain lubricant and rust inhibitor.

### Super Lube® Lightweight Oil Typical Applications:

- ▶ General light oil applications
- ▶ Textile spindles
- ▶ Grinder arbor bearings
- ▶ Ring oiled bearings
- ▶ Wick feeds
- ▶ Bottle and air line oilers
- ▶ Oil cups
- ▶ Enclosed chains
- ▶ Light circulating systems
- ▶ Food grade chain lubricant



Synco Chemical Corporation - Super Lube®  
24 DaVinci Drive, Bohemia, NY 11716  
Tel: (631) 567-5300 / Fax: (631) 567-5359  
Email: [info@super-lube.com](mailto:info@super-lube.com) / [www.super-lube.com](http://www.super-lube.com)





# SUPER LUBE® LIGHTWEIGHT OIL

## Benefits:

- ▶ Viscosity stable
- ▶ Non-toxic (USDA Rating H-1)
- ▶ Long Lasting
- ▶ Reduces friction and wear
- ▶ Waterproof
- ▶ Superior at low temperatures
- ▶ Prevents rust and corrosion



Typical Properties		
Test	Test Method	Rating
Color		Translucent
Viscosity	ASTM D445	
cSt @ 100°C		8-10
cSt @ 40°C		50-70
Temperature Range		-40°F to 500°F
ISO grade		100
Replaces ISO grades		46-100
Replaces SAE grade oils		80W
Viscosity index		145
Shelf life		24 months

While the information contained herein is believed to be reliable, Synco Chemical Corporation Chemical Corporation makes no representation as to the reliability of the results the buyer or user will achieve.

Part No.	Description
52004	4 oz Bottle
52020	1 Pint
52030	1 Quart
52040	1 Gallon
52050	5 Gallon
52550	55 Gallon



Synco Chemical Corporation - Super Lube®  
 24 DaVinci Drive, Bohemia, NY 11716  
 Tel: (631) 567-5300 / Fax: (631) 567-5359  
 Email: [info@super-lube.com](mailto:info@super-lube.com) / [www.super-lube.com](http://www.super-lube.com)

