



SYNCO CHEMICAL CORPORATION



Super Lube® Grommet Lubricant

Super Lube® Grommet lubricant will assist in the attachment and insertion of rubber and soft plastic parts where there is a tight fit.

Super Lube® Grommet lubricant is an aqueous polymeric solution that is non-flammable, has a wide operating temperature range, low coefficient of friction, and dries clean offering superior temporary lubrication and will not leave any residue ensuring the part will function according to the original specification.

Super Lube® Grommet lubricant is compatible with most plastics and rubber such as Buna, EPDM, Neoprene, Nitrile, Viton, Butadiene, Butyl, Natural Rubber, LDPE, MDPE, HDPE, Polypropylene, PVC, Polyurethane, ABS, and Nylon.

Super Lube® Grommet Lubricant are used on the following applications:

Grommets	Diaphragms	Hoses
Bumpers	Sleeves	Plugs
Washers	Tires	Seals
O-Rings	Bushings	Belts
Boots	ABS Brackets	Shock and Vibration Mounts

Super Lube® Grommet lubricant will speed up your assembly process and assist you in achieving increased throughput without damaging component parts.



SYNCO CHEMICAL CORPORATION



Key Features:

Increase production by speeding up assembly work
 Wide temperature range (-15F to 220F)
 Provides superior lubrication
 Low coefficient of Friction

Dries clean without any residue
 Non-toxic, biodegradable, non-flammable
 compatible with most plastic and rubber components
 Available in two viscosities depending on your application

Typical Properties:

Testing Characteristic

Operating Temperature Range

Color/ Appearance

Typical Viscosity of Grommet Lube light (Spindle H1,RPM 100)

Typical viscosity of Grommet Lube Heavy. (Spindle H1,RPM 100)

Flammability

PH of material

Coefficient of Friction

Typical Result

-15F to 220F

Orange

70-100 CPS

140-180 CPS

Non Flammable

6.5 – 7.5

0.0140 Static / 0.096 Dynamic

Super Lube® Grommet Lubricant is available in many sizes from quarts to 55 gallon drums. Please consult with your authorized Super Lube® distributor for pricing and availability. **Synco Chemical Corporation 800 253 5823.** www.super-lube.com

SYNCO CHEMICAL CORPORATION

..... *Super Lube® ..."everywhere and no wear"!*